

メモ

メモです。

コマンド

```
sudo nano -w /etc/hosts
# 以下の行を加える
#192.168.99.1 server.mycluster.home server
#192.168.99.5 ssi1.mycluster.home ssi1
#192.168.99.6 ssi2.mycluster.home ssi2
#192.168.99.7 ssi3.mycluster.home ssi3
#192.168.99.8 ssi4.mycluster.home ssi4
sudo apt-get install ¥
git kernel-package xsltproc¥
automake autoconf libtool pkg-config
mkdir -p /kerrighed-3.0.0
cd /kerrighed-3.0.0
git clone ¥
git://mirrors.git.kernel.org/cluster/kerrighed/kernel
git clone ¥
git://mirrors.git.kernel.org/cluster/kerrighed/tools
cd kernel
make-kpkg --config menuconfig ¥
--rootcmd fakeroot kernel-image
cd ..
sudo dpkg -i linux-image-2.6.30-kg_2.6.30-kg-10.00.Custom_amd64.deb
cd tools
./autogen.sh
./configure --disable-kernel --sysconfdir=/etc
perl -i -ple 's/ ¥-¥-nonet//g;' man/Makefile
make
cd /NFSROOT/kerrighed
su
chroot /NFSROOT/kerrighed
passwd
mount -t proc none /proc
dpkg -i /home/shimotsuki/kerrighed-3.0.0/linux-image-2.6.30-kg_2.6.30-kg-10.00.Custom_amd64.deb
cd /home/shimotsuki/kerrighed-3.0.0/tools
make install
apt-get install dhcp3-common nfs-common open-iscsi ocfs2-tools
nano -w /etc/iscsi/iscsid.conf
# 変更点は以下
#node.startup = automatic
#node.session.auth.authmethod = CHAP
#node.session.auth.username = username
#node.session.auth.password = password
#discovery.sendtargets.auth.authmethod = CHAP
#discovery.sendtargets.auth.username = username
#discovery.sendtargets.auth.password = password
nano -w /etc/default/o2cb
# 変更点は以下
#O2CB_ENABLED=true
#O2CB_BOOTCLUSTER=ocfs2
cp ¥
/usr/share/doc/ocfs2-tools/examples/cluster.conf ¥
/etc/ocfs2/
nano -w /etc/ocfs2/cluster.conf
rm /etc/mtab
ln -s /proc/mounts /etc/mtab
nano -w /etc/fstab
# 以下の内容にする
#none /proc proc defaults 0 0
#none /sys sysfs defaults 0 0
#none /config configfs defaults 0 0
#none /var/run tmpfs defaults 0 0
#LABEL=OCFS2 /work ocfs2 _netdev 0 0
exit
exit
```